TObject

fUniqueID
fBits
fgDtorOnly
fgObjectStat
kCanDelete
kMustCleanup
kObjInCanvas
kIsReferenced
kHasUUID
kCannotPick
kNoContextMenu
kInvalidObject
kIsOnHeap
kNotDeleted
kZombie
kBitMask
kSingleKey
kOverwrite
kWriteDelete
fgIsA

@~TObject
MakeZombie
DoError
TObject
TObject
operator=
AppendPad
Browse
ClassName
Clear
Clone
Compare
Copy
Delete
DistancetoPrimitive
Draw
DrawClass
DrawClone
Dump
Execute
Execute
ExecuteEvent
FindObject
FindObject
GetDrawOption
GetUniqueID
GetName
GetIconName
GetOption
GetObjectInfo
GetTitle
HandleTimer
Hash
InheritsFrom
InheritsFrom
Inspect
IsFolder
IsEqual
IsSortable
IsOnHeap
IsZombie
Notify
Is
Paint
Pop
Print
Read
RecursiveRemove
SavePrimitive
SetDrawOption
SetUniqueID
UseCurrentStyle
Write
Write
operator new
operator new@[@]
operator new
operator new@[@]
operator delete
operator delete@[@]
operator delete
operator delete@[@]
SetBit
SetBit
ResetBit
TestBit
TestBits
InvertBit
Info
Warning
Error
SysError
Fatal
AbstractMethod
MayNotUse
GetDtorOnly
SetDtorOnly
GetObjectStat
SetObjectStat
Class
Class_Name
IsA
ShowMembers

TXMLParser

fContext
fValidate
fStopError
fValidateError
fValidateWarning
fParseCode
fgIsA

@~TXMLParser
InitializeContext
ReleaseUnderlying
OnValidateError
OnValidateWarning
StopParser
SetParseCode
SetValidate
GetValidate
ParseFile
ParseBuffer
GetParseCode
GetParseCodeMessage
SetStopOnError
GetStopOnError
GetValidateError
GetValidateWarning
Class
Class_Name
IsA
ShowMembers

TQObject

fListOfSignals
fListOfConnections
fgIsA

@~TQObject
GetSender
GetSenderClassName
ConnectToClass
ConnectToClass
CheckConnectArgs
TQObject
operator=
TQObject
GetListOfClassSignals
GetListOfSignals
GetListOfConnections
EmitVA
EmitVA
Emit
Emit
Emit
Emit
Emit
Emit
Emit
Emit
Emit
Emit
Emit
Emit
Emit