## TObject

| | | |
|---|---|---|
| fUniqueID | kIsReferenced | kZombie |
| fBits | kHasUUID | kBitMask |
| fgDtorOnly | kCannotPick | kSingleKey |
| fgObjectStat | kNoContextMenu | kOverwrite |
| kCanDelete | kInvalidObject | kWriteDelete |
| kMustCleanup | kIsOnHeap | fgIsA |
| kObjInCanvas | kNotDeleted | |

| | | |
|---|---|---|
| @~TObject | GetOption | operator new |
| MakeZombie | GetObjectInfo | operator new@[@] |
| DoError | GetTitle | operator delete |
| TObject | HandleTimer | operator delete@[@] |
| TObject | Hash | operator delete |
| operator= | InheritsFrom | operator delete@[@] |
| AppendPad | InheritsFrom | SetBit |
| Browse | Inspect | SetBit |
| ClassName | IsFolder | ResetBit |
| Clear | IsEqual | TestBit |
| Clone | IsSortable | TestBits |
| Compare | IsOnHeap | InvertBit |
| Copy | IsZombie | Info |
| Delete | Notify | Warning |
| DistancetoPrimitive | ls | Error |
| Draw | Paint | SysError |
| DrawClass | Pop | Fatal |
| DrawClone | Print | AbstractMethod |
| Dump | Read | MayNotUse |
| Execute | RecursiveRemove | GetDtorOnly |
| Execute | SavePrimitive | SetDtorOnly |
| ExecuteEvent | SetDrawOption | GetObjectStat |
| FindObject | SetUniqueID | SetObjectStat |
| FindObject | UseCurrentStyle | Class |
| GetDrawOption | Write | Class_Name |
| GetUniqueID | Write | IsA |
| GetName | operator new | ShowMembers |
| GetIconName | operator new@[@] | |

## TDrawFeedback

fAll
fNames
fOption
fProof
fgIsA

@~TDrawFeedback
TDrawFeedback
Feedback
SetOption
Class
Class_Name
IsA
ShowMembers

## TQObject

fListOfSignals
fListOfConnections
fgIsA

@~TQObject
GetSender
GetSenderClassName
ConnectToClass
ConnectToClass
CheckConnectArgs
TQObject
operator=
TQObject
GetListOfClassSignals
GetListOfSignals
GetListOfConnections
EmitVA
EmitVA
Emit
Emit
Emit
Emit
Emit
Emit
Emit
Emit
Emit
Emit
Emit
Emit
Emit
Emit
Emit
Connect
Disconnect
HighPriority
LowPriority
HasConnection
NumberOfSignals
NumberOfConnections
Connected
Disconnected
Destroyed
ChangedBy
Message
Connect
Connect
Disconnect
Disconnect
LoadRQ_OBJECT
Class