QObject

staticMetaObject · staticQtMetaObject
staticMetaObjectExtraData
d_ptr

metaObject	connect
qt_metacast	connect
tr	disconnect
trUtf8	disconnect
tr	disconnect
trUtf8	disconnect
qt_metacall	dumpObjectTree
qt_static_metacall	dumpObjectInfo
d_func	setProperty
d_func	property
QObject	dynamicProperty
@~QObject	registerUserData
event	setUserData
eventFilter	userData
objectName	destroyed
setObjectName	parent
isWidgetType	inherits
signalsBlocked	deleteLater
blockSignals	sender
thread	senderSignalIndex
moveToThread	receivers
startTimer	timerEvent
killTimer	childEvent
children	customEvent
setParent	connectNotify
installEventFilter	disconnectNotify
removeEventFilter	isObject
connect	

QWidget

staticMetaObject · staticQtMetaObject · create · setWindowBackground · setChildrenIgnoreMask · data

metaObject	maximumSize	unsetCursor	unsetLocale	showMaximized	focusWidget	enterEvent
qt_metacast	minimumWidth	setMouseTracking	isRightToLeft	showFullScreen	nextInFocusChain	leaveEvent
tr	minimumHeight	hasMouseTracking	isLeftToRight	showNormal	previousInFocus	paintEvent
trUtf8	maximumWidth	underMouse	setFocus	close	acceptDrops	moveEvent
tr	maximumHeight	setMask	isActiveWindow	raise	setAcceptDrops	resizeEvent
trUtf8	setMinimumSize	setMask	activateWindow	lower	addAction	closeEvent
qt_metacall	setMinimumSize	clearMask	clearFocus	stackUnder	addActions	contextMenuEvent
qt_static_metacall	setMaximumSize	clearMask	setFocus	move	insertAction	tabletEvent
d_func	setMaximumSize	sender	focusPolicy	move	insertActions	actionEvent
d_func	setMinimumWidth	d_func	setFocusPolicy	resize	removeAction	dragEnterEvent
QWidget	setMinimumHeight	graphicsEffect	hasFocus	resize	actions	dragMoveEvent
@~QWidget	setMaximumWidth	setGraphicsEffect	setTabOrder	setGeometry	parentWidget	dragLeaveEvent
devType	setMaximumHeight	grabGesture	setFocusProxy	setGeometry	setWindowFlags	dropEvent
winId	sizeIncrement	ungrabGesture	focusProxy	saveGeometry	windowFlags	showEvent
createWinId	setSizeIncrement	setWindowTitle	contextMenu	restoreGeometry	overrideWindowFlags	hideEvent
internalWinId	setSizeIncrement	setStyleSheet	setContextMenu	adjustSize	windowType	x11Event
effectiveWinId	baseSize	styleSheet	grabMouse	isVisible	find	changeEvent
style	setBaseSize	windowTitle	grabMouse	isVisibleTo	childAt	metric
setStyle	setBaseSize	setWindowIcon	releaseMouse	isHidden	childAt	inputMethodEvent
isTopLevel	setFixedSize	windowIcon	grabKeyboard	isMinimized	x11Info	inputMethodQuery
isWindow	setFixedSize	setWindowIconText	releaseKeyboard	isMaximized	x11PictureHandle	inputMethodHints
isModal	setFixedWidth	windowIconText	grabShortcut	isFullScreen	handle	setInputMethodHints
windowModality	setFixedHeight	setWindowRole	releaseShortcut	windowState	setAttribute	resetInputContext
setWindowModality	mapToGlobal	windowRole	setShortcutEnabled	setWindowState	testAttribute	updateMicroFocus
isEnabled	mapFromGlobal	setWindowFilePath	setShortcut	overrideWindowState	paintEngine	create
isEnabledTo	mapToParent	windowFilePath	mouseGrabber	sizeHint	ensurePolished	destroy
isEnabledToTLW	mapFromParent	setWindowOpacity	keyboardGrabber	minimumSizeHint	inputContext	focusNextPrevChild
setEnabled	mapTo	windowOpacity	updatesEnabled	sizePolicy	setInputContext	focusNextChild
setDisabled	mapFrom	isWindowModified	setUpdatesEnabled	setSizePolicy	isAncestorOf	focusPreviousChild
setWindowModified	window	setToolTip	graphicsProxyWidget	setSizePolicy	autoFillBackground	QWidget
frameGeometry	nativeParentWidget	toolTip	update	heightForWidth	setAutoFillBackground	styleAttribute_helper
geometry	topLevelWidget	setStatusTip	repaint	visibleRegion	setWindowSurface	updateLayout
normalGeometry	palette	statusTip	update	setContentsMargins	windowSurface	QWidget
x	setPalette	setWhatsThis	update	setContentsMargins	windowContext	contextMenuRequested
y	setBackgroundRole	whatsThis	update	getContentsMargins	actionContext	styleChange
pos	backgroundRole	accessibleName	repaint	contentsMargins	mousePressEvent	enabledChange
frameSize	setForegroundRole	setAccessibleName	repaint	contentsRect	mouseReleaseEvent	paletteChange
size	foregroundRole	accessibleDescription	repaint	layout	mouseDoubleClickEvent	fontChange
width	font	setAccessibleDescription	setVisible	setLayout	mouseMoveEvent	
height	setFont	setLayoutDirection	setHidden	updateGeometry	wheelEvent	
rect	fontMetrics	layoutDirection	show	setParent	keyPressEvent	
childrenRect	fontInfo	unsetLayoutDirection	hide	setParent	keyReleaseEvent	
childrenRegion	cursor	setLocale	setShown	scroll	focusInEvent	
minimumSize	setCursor	locale	showMinimized	scroll	focusOutEvent	

TQRootCanvas

staticMetaObject
staticMetaObjectExtraData
fContextMenu
fCanvas
fWid
fNeedResize
fIsCanvasOwned
fParent
fTabWin
fgIsA

QPaintDevice

PdmWidth	PdmWidthMM	PdmNumColors	PdmDpiX	PdmPhysicalDpiX	PdmNumColors
PdmHeight	PdmHeightMM	PdmDepth	PdmDpiY	PdmPhysicalDpiY	

@~QPaintDevice	paintEngine	widthMM	logicalDpiY	numColors	QPaintDevice
devType	width	heightMM	physicalDpiX	colorCount	metric
paintingActive	height	logicalDpiX	physicalDpiY	depth	